

HFBC80-W/KS - DC/DC CONVERTER WITH LATEST TECHNOLOGY IN COMPACT DESIGN!



HFBC80-W/KS

Autronic presents the fully encapsulated HFBC80-W/Ks for chassis mounting. The new converter in the familiar compact housing offers an ultra-wide input voltage range from 14.4 V to 154 V with 80 Watt power now. This is a 33 % power increase compared to the previous version. A single converter thus covers all internal on-board voltages for railway (24 V, 36 V, 72 V and 110 V), including the tolerance range of +/- 40 % required by EN 50155, in a single device. This ultra-wide solution is therefore ideal for companies operating worldwide to perform the qualification of own applications cost-efficiently with one converter.

The EN 50155 regarding temperature, shock, vibration, as well as the railroad specific criteria for EMC according to EN50121-3-2, as well as Surge, Burst and ESD are completely complied without any additional components. In addition, the converter has an integrated hold up time of 10 ms (class S2), which makes the compact converter (113 x 46 x 35 mm) unique, designed according to temperature class OT4, ST1+2 (-40...85 °C). Very high efficiency (up to 92%) is achieved by combining booster and active clamp at the optimized operating point.

An inrush current limitation, overvoltage and overtemperature protection and an active reverse polarity protection are integrated as standard. In addition, the converter is open-circuit protected and permanently short-circuit proof. The modules can be connected in parallel and the output voltage can be trimmed.

The fire and smoke requirement according to EN 45545-2 (Hazard Level 3, R24/R25) is met.

Currently the DC/DC converter is available with an output voltage of 12 V and 24 V, further outputs are available on request.

March 2023

For queries:

Giovanni Rodio

Tel: +49 (0) 7147/24-232

giovanni.rodio@autronic.de

AUTRONIC Steuer- und Regeltechnik GmbH

Siemensstr. 17

D-74343 Sachsenheim

Telefon: +49 (0) 71 47 / 24-200

Telefax: +49 (0) 71 47 / 24-252

Homepage: www.autronic.de

E-Mail: vertrieb@autronic.de